RT Alpha

(non binding picture)

Composition

1 scoreboard
1 control console
1 Keyboard
1 carrying case for control console
1 mains cable (5m)
Junction box and transmission cables (for cable controlled version)
Operating and installation instructions

Description

Use:	Indoor
Transmission:	Radio (868 MHz) or cable
Readability:	60m, angle >160°
Dimensions:	2400 x 700 x 90mm
Weight:	27 kg
Power supply:	230V / 50-60Hz **Power consumed**: 92 VA
Protection:	Unbreakable mat polycarbonate front face (DIN 18032-3)
Mains cable (supplied):	5 m – Type: 230V, 3G, 0.75 mm²
Cable controlled:	For cable controlled models or radio controlled models with cable set: Junction Box + 50 m transmission cable (scoreboard/junction box) – Type: phone cable 2 pairs 6/10th + 10 m transmission cable DIN/DIN (junction box/console)

Display functions

Player names:	2 x 10 characters (12 cm)
Message display:	*1st Line:* Running messages:
	=>1 message of 1000 characters
	=> or 2 messages of 500 characters
	=> or 4 messages of 250 characters
	Programmable number of rotations
	Programmable order to display messages (if several)
	2nd Line: Fixed message => 10 characters
Score:	2 x 2 red LED digits (16 cm): 15-30-40-A
Set results:	1st & 2nd set: 1 red LED (16 cm) digit per player: from 0 to 7
	3rd set: 2 red LED (16 cm) digits per player
Service side:	2 red LED arrows
Adjustable luminosity	9 luminosity levels

Control consoles

1 console: (340 x 175 x 60 mm) with LCD screen with 2 lanes of 20 characters (9mm high)
1 charger (radio): Hold the consoles in charge when there are not in use. (Autonomy max 16 h)
USB Port: For program update or connect PC keyboard
Programme: Tennis and free mode for sports with sets (Pelota, beach volley…)
Multilingual Programme
Message display: Latin, Cyrillic and Arabic letters

Options

TV Interface (RS 485): Data transmission for TV broadcasting
Cable set: Cable mode for radio controlled scoreboard
Model available with Player Hand Held Console (radio) to add points
Wheeled stand